

# Product data sheet

Specifications



## APC Back-UPS 1200VA, 230V, AVR, 4 universal & 1 IEC outlets

BX1200MI-MS

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	230 V
Rated power in W	650 W
Rated power in VA	1200 VA
Output connection type	4 universal 1 IEC 60320 C13
Cable length	1.22 m
Number of cables	1
Battery type	Lead-acid battery

### Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Battery voltage	12 V
Battery power in VAh	99 VAh runtime 108 VAh capacity
Battery life	3...5 year(s)
Replacement battery	<a href="#">APCRBC175</a>
Battery graph comments	Curve fit to measured runtime data. All measurements taken with new, fully charged batteries, at typical environmental conditions, with no electrical input and balanced resistive load (PF = 1.0) output.
Extended runtime	0

### General

Provided equipment	user manual
Max runtime	120 min
Number of power module free slots	0
Number of power module filled slots	0

Redundant	No
-----------	----

## Physical

Colour	Black
Height	19 cm
Width	14 cm
Depth	39 cm
Net weight	7.6 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

## Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	140...300 V
Input Power Factor at Full Load	0.54

## Output

Maximum configurable power in W	650 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Full load runtime	00:01:00 650 W
Half load runtime	00:05:00 300 W
Maximum configurable power in VA	1200 VA
Transfer time	6 ms typical : 10 ms maximum

## Conformance

Product certifications	CE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Equipment protection policy	Lifetime : 50000 euros

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...3000 m
Acoustic level	40 dBA

---

IP degree of protection	IP20
-------------------------	------

---

## Communications & Management

---

Control panel	LED Status display with on line : on battery
---------------	--

---

## Surge Protection and Filtering

---

Surge energy rate	273 J
-------------------	-------

---

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	29.7 cm
------------------	---------

Package 1 Width	49.5 cm
-----------------	---------

Package 1 Length	23.5 cm
------------------	---------

Package 1 Weight	8.6 kg
------------------	--------

SCC14	10731304410710
-------	----------------

---

## Offer Sustainability

---

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
-------------------	--

Toxic heavy metal free	Yes
------------------------	-----

Mercury free	Yes
--------------	-----

China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
-----------------------	---

RoHS exemption information	<a href="#">Yes</a>
----------------------------	---------------------

---

## Contractual warranty

---

Warranty	2 years repair or replace
----------	---------------------------

## Recommended replacement(s)